## **DECLARATION OF PERFORMANCE**

Nro. 042-FF-2013-10-18

- 1. Unique identification code of the product-type: Extruded polystyrene (XPS) Finnfoam FL400-120
- 2. Allowing identification of the construction product: EAN-Code: 64 18711 24120 1
- 3. **Intended uses of the construction product:** Products are used as thermal insulation. Product applications are specified in the web site <u>www.finnfoam.fi</u>.
- 4. Name, registered trade name and contact address of the manufacturer:

Finnfoam Oy (0689386-6) Satamakatu 5 24100 Salo, Finland Tel. +358 2 777 300 Fax: +358 2 777 3020 Email: <u>finnfoam@finnfoam.fi</u>

- 6. System of attestation of conformity: AVCP 3
- 7. Declaration of performance concerning a construction product covered by a harmonized standard:

VTT Expert Services (NB. 0809) and Institute of thermal insulation of Vilnius Gediminas Technical University (NB. 1688) performed initial type testing under system 3 and issued test/calculation reports.



## 9. Declared performance:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	E	EN 13164:2012 EN 14934:2007
Long term water absorption by total immersion	WL(T)0,7	
Long term water absorption by diffusion	WD(V)1	
Release of dangerous substances	No releases	
Thermal resistance RD (m²K)/W	3,25	
Thermal conductivity λο W/(mK)	0,037	
Thickness	T1	
Water vapour transmission	NPD	
Compressive strength	CS(10\Y)300	
Tensile strength	NPD	
Dimensional stability	DS(70,90)	
Freeze-thaw resistance	FTCD1	
Compressive creep	CC(2/1,5/50)180	
Cyclic loading	NPD	

## Safety data sheet: www.finnfoam.fi/kayttoturvallisuustiedote

Signed for and on behalf of the manufacturer by:

Henri Nieminen, CEO

Salo 18.10.2013

61 4

(signature)



## **Declaration of Performance**