DECLARATION OF PERFORMANCE

Nro. 005-FF-2014-04-14

- 1. Unique identification code of the product-type: Extruded polystyrene (XPS) Finnfoam FL-300/100
- 2. Allowing identification of the construction product: EAN-Code: 64 18711 23100 4
- 3. **Intended uses of the construction product:** Products are used as thermal insulation. Product applications are specified in the web site <u>www.finnfoam.fi</u>.
- 4. Name, registered trade name and contact address of the manufacturer:

Finnfoam Oy (0689386-6) Satamakatu 5 24100 Salo, Finland Tel. +358 2 777 300 Fax: +358 2 777 3020 Email: <u>finnfoam@finnfoam.fi</u>

- 6. System of attestation of conformity: AVCP 3
- 7. Declaration of performance concerning a construction product covered by a harmonized standard:

VTT Expert Services (NB. 0809) and Institute of thermal insulation of Vilnius Gediminas Technical University (NB. 1688) performed initial type testing under system 3 and issued test/calculation reports.



9. Declared performance:

| Essential characteristics | Performance | Harmonized technical specification |
|--|-----------------|------------------------------------|
| Reaction to fire | F | EN 13164:2012 EN 14934:2007 |
| Long term water absorption by total immersion | WL(T)0,7 | |
| Long term water absorption by diffusion | WD(V)2 | |
| Release of dangerous substances | No releases | |
| Thermal resistance RD (m ² K)/W | 2,70 | |
| Thermal conductivity λο W/(mK) | 0,037 | |
| Thickness | T1 | |
| Water vapour transmission | NPD | |
| Compressive strength | CS(10\Y)250 | |
| Tensile strength | NPD | |
| Dimensional stability | DS(70,90) | |
| Freeze-thaw resistance | FTCD1 | |
| Compressive creep | CC(2/1,5/50)130 | |
| Cyclic loading | NPD | |

Safety data sheet: www.finnfoam.fi/kayttoturvallisuustiedote

Signed for and on behalf of the manufacturer by:

Henri Nieminen, CEO

Salo 14.4.2014

(signature)



Declaration of Performance