

## DECLARATION OF PERFORMANCE

Nro. 002-FF-2016-01-04

1. **Unique identification code of the product-type:** Extruded polystyrene (XPS) Finnfoam FI300, FI300P, FI300URA, FL300, FL300P, CW300, FK300.
2. **Allowing identification of the construction product:** See product label.
3. **Intended uses of the construction product:** Products are used as thermal insulation. Product applications are specified in the web site [www.finnfoam.fi](http://www.finnfoam.fi).
4. **Name, registered trade name and contact address of the manufacturer:**

Finnfoam Oy (0689386-6)  
Satamakatu 5  
24100 Salo, Finland  
Tel. +358 2 777 300  
Fax: +358 2 777 3020  
Email: [finnfoam@finnfoam.fi](mailto:finnfoam@finnfoam.fi)

6. **System of attestation of conformity:** System 3
7. **Declaration of performance concerning a construction product covered by a harmonized standard:**

VTT Expert Services (NB. 0809) and Institute of thermal insulation of Vilnius Gediminas Technical University (NB. 1688) performed initial type testing under system 3 and issued test/calculation reports.

**FINNFOAM**<sup>®</sup>  
MAAN PARAS ERISTE

8. Declared performance:

Essential characteristics	Performance			Harmonised technical specification
Thermal resistance	Thickness tolerance	T1		EN 13164:2012 + A1:2015
	Thickness (mm)	Thermal conductivity $\lambda_D$	Thermal resistance $R_D$	
	20	0,033	0,60	
	30	0,033	0,90	
	40	0,035	1,15	
	50	0,035	1,45	
	60	0,035	1,70	
	70	0,035	2,00	
	80	0,037	2,15	
	100	0,037	2,70	
120	0,037	3,25		
Reaction to fire	Reaction to fire	F		EN 13164:2012 + A1:2015
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics	NPD		
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance $R_D$ and thermal conductivity $\lambda_D$	No change		
	Durability characteristics	DS(70,90)		
Compressive strength	Copressive stress or compressive strength	20mm	CS(10\Y)200	
		$\geq 30$ mm	CS(10\Y)250	
	Deformation under specified compressive load and temperature conditions	NPD		
Tensile/ Flexural/ Shear strength	Bending strength	NPD		
	Tensile strength perpendicular to faces	NPD		

# Declaration of Performance

	Shear strength	NPD
<b>Durability of compressive strength against ageing and degradation</b>	Compressive creep $\geq 30\text{mm}$	CC(2/1,5/50)130
	Cyclic loading	NPD
	Freeze-thaw resistance	FTCD1
<b>Water permeability</b>	Long term water absorption after total immersion	WL(T)0,7
	Long term water absorption after diffusion	WD(V)1
<b>Water vapour permeability</b>	Water vapour transmission	NPD
<b>Release of dangerous substances to the indoor environment</b>	Release of dangerous substances	No releases
<b>Continuous glowing combustion</b>	Continuous glowing combustion	NPD

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Safety data sheet: [www.finnfoam.fi/kayttoturvallisuustiedote](http://www.finnfoam.fi/kayttoturvallisuustiedote)**

Signed for and on behalf of the manufacturer by:

Henri Nieminen, CEO

Salo 4.1.2016



(signature)

**FINNFOAM®**  
MAAN PARAS ERISTE