



# DECLARATION OF PERFORMANCE

Nro. 001-FF-2020-04-29

1. **Unique identification code of the product-type:** Extruded polystyrene (XPS) Finnfoam FI200, FI200P, FL200, FL200P.

2. **Allowing identification of the construction product:** See product label.

3. **Intended uses of the construction product:** Products are used as thermal insulation.

4. **Name, registered trade name and contact address of the manufacturer:**

Finnfoam Oy (0689386-6)

Satamakatu 5

24100 Salo, Finland

Tel. +358 2 777 300

Fax: +358 2 777 3020

Email: [finnfoam@finnfoam.fi](mailto:finnfoam@finnfoam.fi)

6. **System of attestation of conformity:** AVCP 4 for reaction to fire and AVCP 3 for other characteristics.

7. **Declaration of performance concerning a construction product covered by a harmonized standard:** Eurofins Expert Services (NB. 0809) and Institute of thermal insulation of Vilnius Gediminas Technical University (NB. 1688) performed initial type testing under system 3 and issued test/calculation reports.



8. Declared performance:

Essential characteristics	Performance		Harmonised technical specification
	Thickness tolerance	T1	
	Thickness (mm)	Thermal conductivity $\lambda_D$	Thermal resistance $R_D$
	50	0,035	1,45
	70	0,035	2,00
	100	0,037	2,70
Reaction to fire	Reaction to fire	NPD	
Durability of reaction to fire against heat, weathering, ageing/degradation	Durability characteristics	No change	
Durability of thermal resistance against heat, weathering, ageing/degradation	Thermal resistance $R_D$ and thermal conductivity $\lambda_D$	No change	
	Durability characteristics	DS(70,90)	
Compressive strength	Compressive stress or compressive strength	CS(10\Y)200	
	Deformation under specified compressive load and temperature conditions	NPD	
Tensile/ Flexural/ Shear strength	Bending strength	NPD	
	Tensile strength perpendicular to faces	NPD	
	Shear strength	NPD	
Durability of compressive strength against ageing and degradation	Compressive creep	CC(2/1,5/50)90	
	Cyclic loading	NPD	
	Freeze-thaw resistance	FTCD2	
Water permeability	Long term water absorption after total immersion	WL(T)0,7	

EN  
13164:2012  
+ A1:2015



	Long term water absorption after diffusion	WD(V)1	
<b>Water vapour permeability</b>	Water vapour transmission $\mu$	150	
<b>Release of dangerous substances to the indoor environment</b>	Release of dangerous substances	No releases	
<b>Continuous glowing combustion</b>	Continuous glowing combustion	NPD	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

**Safety data sheet: [www.finnfoam.fi/kayttoturvallisuustiedote](http://www.finnfoam.fi/kayttoturvallisuustiedote)**

Signed for and on behalf of the manufacturer by:

Henri Nieminen, CEO

Salo 29.4.2020

---

(signature)